

Manual callpoint, flush mount, green, free contact, break glass

DMN700G

The DMN700G is a green manual call point for flush mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 breakable glass and test key. Surface mount applications require the addition of the DM788G or DMN787G.

Specifications

Cable Termination	0.5 - 2.5 mm ²
Max. contact rating (resistive load)	2A @ 30 VDC
Mechanical	
Material	PC/ABS
Weight	110g
Colour	Green
Environmental	
Operating temperature	-10°C to +55°C
Storage temperature	-10°C to +55°C
Relative humidity (non-condensing)	0-95%
IP Rating	IP24D

Ordering Information

DMN700G	Manual callpoint, flush mount, green, free contact, break glass
DMN787G	Surface mounting box with earth connector, green
DM788GR	Surface mount box without connectors, GREEN
DM711	EN54 universal glass ARITECH branded
DM715	EN54 Universal MCP Glass (without branding)
DMN782	Hinged transparent MCP protection cover
DMN784	Call Point Test Key
DMN798	Breakable Seal for Manual Call Points
DMN800	Resettable Element for Manual Call Point



- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards