



- 9 Programmable Dial-out Numbers for each Trigger
- Separate programmable Voice Messages or SMS sent to some or all phone numbers on trigger
- Programmable Dial-out/SMS delay after trigger
- Programmable Trigger "runaway protection" – ability to limit no of dial outs/SMSs to 50 in any 24 hour period
- Trigger inputs can be programmable as instant or "double knock" (2 activations needed within 60 secs)
- Removeable Antenna allows replacement with remote Antenna plus cable to optimize GSM reception
- Built-in microphone
- Built-in "Listen-in". Opens up after trigger or via dial-in
- Built-in Memory for programmed settings
- "Pay as you go" SIM low credit indication
- Battery back-up
- Dialer can send an SMS with its programmed details
- Dialer outputs can be programmed as User activated only or User activated + Trigger/Event follow activated
- Outputs can be programmed as toggle latching On/Off or momentary
- Activate outputs remotely via dial-in, SMS or free APP
- Network Provider Field Strength Indicator

Model No: AD-06

Connect to any Alarm Panel or Triggered Relay Output

6 Trigger Inputs – 4 Outputs

Back-lit LCD shows text in any of 8 languages

Program using either the built-in keypad or remotely via SMS or a free APP

Programmable as either a Silent (dial-out only) or Audible Alarm

Cancel Dial-out and Alarm at remote Tel



Keystone Electronics Limited

The Colmore Building, 20 Colmore Circus
Queensway, Birmingham B4 6AT